



# OmniAire MiniForce II

## HEPA Air Filtration Machine



### ORDERING INFO

	PART NUMBER
OmniAire MiniForce	MF100C
OmniAire MiniForce 99.99% 0.3μ	MF100CMED
Primary/Secondary Two-Stage Filters (box of 20)	MFP1313
HEPA Filter 99.99%, 0.3μ (metal frame)	MFH12G
HEPA FILTER 99.97%, 0.3μ (pb frame)	MFH12
OdorGuard 600 Carbon Filter	OG1212
Intake Manifold Kit (Manifold, Clamp & 3' Duct)	MFIM8KIT
ABS Plastic Intake Manifold, 8" Dia.	MFIM8
Quick Clamp, 8"-10" Dia.	QCW12
Flexible Duct, 8" Dia. x 25' L	MD8



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

The MiniForce II is a compact, portable HEPA air scrubber built on aircraft-grade aluminum housing, with four non-marking rubber casters, for easy deployment at your jobsite. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. It can be used with multiple filter options such as HEPA, activated carbon plus MERV 9 primary/secondary filter. Additional accessories include intake manifold, flex ducting and quick clamps.

### OmniAire MiniForce II

<b>Airflow*</b>	325/375 CFM
<b>Power Requirements</b>	115VAC/60 Hz/1.6 Amp
<b>Motor</b>	1/5 HP with thermal overload
<b>Controls</b>	speed selector switch - HIGH/OFF/LOW, 0-3" W.C. pressure gauge
<b>Filtration</b>	HEPA filter 99.97% e0.3μ; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon filter; HEPA filter 99.99% 0.3μ
<b>Housing</b>	aircraft grade aluminum; silicone sealed before riveting; 8" outlet; (1) rubber grip handle; (4) 3" hospital grade locking casters
<b>Size/Weight</b>	15"W x 18"H x 27"L; 45 lbs.

\*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.