



OmniAire 2200UL

HEPA Air Filtration Machine



ORDERING INFO

- OmniAire 2000UL
- OmniAire 2000UL 230 VAC
- Primary/Secondary Two-Stage Filters (box of 20)
- HEPA Filter 99.99%, 0.3µ (metal frame)
- HEPA FILTER 99.97%, 0.3µ (pb frame)
- Bag Filter Housing (includes 1 Bag Filter)
- Bag Filter MERV 15
- Vapor Trap V-bank Filter
- OdorGuard 600 Carbon Filter
- ABS Plastic Intake Manifold, 12" Dia.
- Quick Clamp, 12"-16" Dia.
- Flexible Duct, 12" Dia. x 25' L
- Flexible Duct, Wire & Fiber Reinforced

PART NUMBER

- OA2200UL
- OA2200UL230
- OAP2424
- OAH2424G
- OAH2424L
- HBF2200
- OBF10
- OCVT2424
- OG2424D
- OAIM2200-12
- QCW14
- OAD12
- OAD12R



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

OmniAire 2200UL is a negative air machine with two speeds, powerful blower and full size, 12" deep HEPA filter. This is a well-constructed and reliable air scrubber that is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. For VOCs and odor control, VaporTrap or OdorGuard activated carbon filters can be quickly installed. Additional accessories include intake manifold, flex ducting and quick clamps.

OmniAire 2200UL

Airflow*	1000/2000 CFM
Power Requirements	115VAC/60 Hz/11.1 Amp (OA2200UL); also available 230VAC/60Hz (OA2200UL230)
Motor	1.25 HP with thermal overload
Controls	speed switch - HIGH/OFF/LOW; 0-5" W.C. pressure gauge, red indicator light
Filtration	HEPA filter 99.97% @ 0.3µ; MERV 9 primary/secondary filter Optional: MERV 15 bag filter; OdorGuard 600 activated carbon web filter; VaporTrap V-bank filter (36 lbs of active carbon); HEPA filter 99.99% @ 0.3µ
Housing	aircraft grade aluminum with epoxy paint; silicone sealed before riveting; 12" outlet; (4) rubber grip handles; (2) 5" hospital grade locking casters; (2) 5" rigid casters
Size/Weight	28"W x 32"H x 36"L; 138 lbs.

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.