



OmniAire 600 Nitro

HEPA Air Filtration Machine

ORDERING INFO

OmniAire 600 Nitro	OA600N
OmniAire 600 Nitro 230 VAC	OA600N230
OmniAire 600 Nitro GEO w/ MERV 14	OA600NG
Primary/Secondary Two-Stage Filters (box of 20)	OAP1616
HEPA Filter 99.99%, 0.3µ (plastic frame)	OAH15156P
Geo95 MERV 14 Filter	OAG15154
OdorGuard 600 Carbon Filter	OG1616
Quick Clamp, 8"-12" Dia.	QCW12
Flexible Duct, 10" Dia. x 25' L	OAD10
Flexible Duct, Wire & Fiber Reinforced	OAD10R

PART NUMBER



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

The OmniAire Nitro 600 is the best in its class of portable, flame retardant polyethylene air scrubbers. This variable speed machine is built with a powerful motorized impeller with high suction capacity and airflow. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. The Nitro can be used with a variety of filters such as HEPA 99.99%, MERV 14 dust filter and activated carbon filter. Units are safely stackable up to 3 high during operation, transportation, and storage.

OmniAire 600 Nitro

Airflow*	200 - 600 CFM
Power Requirements	115VAC/50-60 Hz/2.4 Amp (OA600N); also available 230VAC/50-60Hz (OA600N230)
Blower	motorized impeller with thermal overload
Recessed Controls	variable speed control; red power indicator light; amber change filter light; GFI protected outlet (8 Amp load max); 12 Amp breaker
Filtration	HEPA Filter 99.99% 0.3µ; MERV 9 primary/secondary filter Optional: OdorGuard 600 carbon web filter; MERV14 GEO95 filter
Housing	polyethylene; 10" inlet/outlet; soft rubber handle
Size/Weight	19"W x 19"H x 25"L; 36 lbs.

**Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.*