



OmniAire 1300V

HEPA Air Filtration Machine

ORDERING INFO

OmniForce II
 Primary/Secondary Two-Stage Filters (box of 20)
 HEPA FILTER 99.97%, 0.3 μ (pb frame)
 OdorGuard 600 Carbon Filter
 ABS Plastic Intake Manifold, 10" Dia.
 Quick Clamp, 10" Dia.
 Flexible Duct, Wire & Fiber Reinforced

PART NUMBER

OA1300V
 OAP2614
 OAH2412
 OG2412D
 OAIM1300-10
 QCW12
 OAD10R



CONFORMS TO UL STD 507
 CERTIFIED TO CAN/CSA STD
 C22.2 NO. 113-M1984

The OmniAire 1300V air scrubber with HEPA filter is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. This machine is only 15" wide and ideal for narrow hallways, hotel rooms and condos. Accessories include activated carbon filters for chemical fumes and biological contaminants, as well as intake manifold, flex ducting and quick clamps.

OmniAire 1300V

| | |
|---------------------------|--|
| Airflow* | 300/1250 CFM |
| Power Requirements | 115 VAC/60 Hz/7.3 Amp |
| Motor | 1 HP with thermal overload |
| Controls | HIGH/OFF/speed control switch; variable speed controller; hour meter; 0-5" W.C. pressure guage |
| Filtration | HEPA 99.97%, 0.3 μ filter; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon filter |
| Housing | aircraft grade aluminum, silicone sealed before riveting; 10" outlet; (4) rubber grip handles; (4) 3" hospital grade locking casters |
| Size/Weight | 15"W x 30"H x 34"L, 693 lbs.; |

**Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.*