



OmniAire 1200PAC

HEPA Air Filtration Machine

ORDERING INFO

OmniAire 1200PAC
 OmniAire 1200PAC 230 VAC
 Pleated Filter MERV 11
 HEPA Filter 99.99%, 0.3µ (metal frame)
 OdorGuard 600 Carbon Filter
 ABS Plastic Intake Manifold, 10" Dia.
 Flexible Duct, 10" Dia. x 25' L
 Quick Clamp 12" Dia.
 Flexible Duct, Wire & Fiber Reinforced

PART NUMBER

OA1200PACM
 OA1200PACM230
 OPF1616
 OAH1616G
 OG1616
 OAIM1200P
 OAD10
 QCW12
 OAD10R



CONFORMS TO UL STD 507
 CERTIFIED TO CAN/CSA STD
 C22.2 NO. 113-M1984

The OmniAire 1200PAC machine is equipped with a medical grade 99.99% HEPA filter and UV-C germicidal lights, which work together to eliminate sub-micron particulates and microbial contamination in healthcare facilities, labs and other critical environments. The 1200PAC features variable air flow, quiet operation, upright housing for a small footprint, and medical grade casters for easy mobility. Additional accessories include PEROx air purification module with hydro-peroxide generators, activated carbon filter, intake/outtake manifold, flex ducting and quick clamps.

OmniAire 1200PAC

Airflow*	200-1100 CFM
Power Requirements	115VAC/60 Hz/7.1 Amp (OA1200PACM); available in 230VAC/60Hz (OA1200PACM230)
UVGI Lights	(4) UV-C 15 watt lamps
Controls	speed switch - LOW/HIGH/MED/Speed Control; variable speed controller; 0-5" W.C. pressure gauge; red power indicator light; UVGI Lights ON/OFF switch; hour meter
Filtration	HEPA filter 99.99% 0.3µ; MERV 11 primary/secondary filter
Housing	aircraft grade aluminum; silicone sealed before riveting; (1) rubber grip handle; (4) 3" hospital grade locking casters
Size/Weight	19"W x 42"H x 22"L; 122 lbs.

**Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.*