



OmniAire 1200V

HEPA Air Filtration Machine

ORDERING INFO

OmniAire 1200V
 OmniAire 1200V 230 VAC
 Primary/Secondary Two-Stage Filters (box of 20)
 HEPA Filter 99.99%, 0.3µ (metal frame)
 HEPA FILTER 99.97%, 0.3µ (pb frame)
 OdorGuard 600 Carbon Filter
 ABS Plastic Intake Manifold, 10" Dia.
 Quick Clamp, 8"-10" Dia.
 Flexible Duct, 10" Dia. x 25' L
 Flexible Duct, Wire & Fiber Reinforced

PART NUMBER

OA1200V
 OA1200V230
 OAP1818
 OAH1616G
 OAH1616
 OG1616
 OAIM1200P
 QCW12
 QCW12
 OAD10R



CONFORMS TO UL STD 507
 CERTIFIED TO CAN/CSA STD
 C22.2 NO. 113-M1984

OmniAire 1200V is an extremely versatile, high performing medium sized HEPA air scrubber. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial or factory sites and medical facilities. The 1200V's upright housing with large 10" wheels for stair climbing makes it easy to transport and setup. This variable speed machine can operate in horizontal or vertical position and meet the needs of your large or small projects. Additional accessories include intake manifold, flex ducting and quick clamps.

OmniAire 1200V

Airflow*	150-1100 CFM
Power Requirements	115VAC/60 Hz/6.1 Amp (OA1200V); also available 230VAC/60Hz (OA1200V230)
Motor	1 HP with thermal overload
Controls	speed switch - HIGH/OFF/Speed Control; variable speed controller; 0-3" W.C. pressure gauge, red indicator light
Filtration	HEPA filter 99.97% @ 0.3µ; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon web filter; HEPA filter 99.99% @ 0.3µ
Housing	aircraft grade aluminum; silicone sealed before riveting; 10" outlet; (1) molded polyurethane handle; (2) 3" hospital grade locking casters; (2) 10" non-marking wheels
Size/Weight	24"W x 39"H x 26"L; 111 lbs.

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.