



Manufacturing Equipment for Abatement
and Restoration Industry Since 1988

OA1200V

HEPA Air Filtration Machine


OmniAire1200V is a high performer for a medium sized HEPA air scrubber. It is used in mold, asbestos, lead abatement and on restoration projects. The variable speed control adjusts the airflow to your requirements. The upright housing with large, 10' wheels for stair climbing, makes it easy to transport and setup. Machine can operate in vertical or horizontal position.

OmniAire 1200V provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

OmniAire 1200V SPECIFICATIONS

Airflow Ratings (cfm)*	150 to 1100
Operating Speeds	Variable
Filtration Stages	HEPA Filter 99.97%, 0.3μ
MERV 8 primary/secondary
Optional	OdorGuard 600 activated carbon filter
Recessed Controls	High/OFF/Speed Control Switch
	Variable speed controller
	Pressure gauge 0-3"W.C.
Motor	3/4 hp with Thermal Overload
Circuit Requirements	115V 60Hz 6.0 amps
Cabinetry	Aluminum, silicone sealed before riveting
Exhaust Collar Diameter	10"
Molded Polyurethane Handle	1
3" Swivel Casters with Breakes	2
10" Non-marking Wheels	2
Net Weight With Filters	105 lbs.
Dimensions	25"Lx24"Wx39"H

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



The OmniAire 1200V comes standard with a particle board 99.97% 0.3μ HEPA filter and can be upgraded to a metal frame 99.99% 0.3μ HEPA filter.



ORDERING INFO PART

OmniAire 1200V	OA1200V
HEPA Filter 99.97%, 0.3μ.....	OAH1616
Primary/Secondary Filter (qty 20) ...	OAP1818
Intake Manifold, 10"	OAIM1200P
Quick Clamp, 10"	QCW12
Flexible Duct, 10" x 25'	OAD10
OdorGuard 600 Carbon Filter	OG1616

Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

Omnitec Design, Inc.

4640 Campus Place, Suite 110 Mukilteo, WA 98275

Visit us @ www.omnitecdesign.com

Office: 425-290-3922