



# The Watchman

## Differential Pressure Monitor

### ORDERING INFO

Watchman  
External Hose Replacement

### PART NUMBER

OWDP  
IOGHOSE10FT

### THE WATCHMAN IS IDEAL FOR

- Abatement/Remediation Jobs
- Restoration Projects
- Construction Sites
- Industrial Areas
- First Response & Epidemic Control
- Bio-Hazard & Crime Scene Clean-up



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

The Watchman is designed for monitoring differential pressure of 0.020" WC in abatement areas. The protective case contains self-calibrating, precise pressure indicator/transmitter with LCD displays and an audible/visual alarm module. The Watchman is easy to setup for operation: plug into power outlet, push the self-calibrate button and connect the pressure tubing from the containment.

### The Watchman

<b>Differential Pressure Range</b>	0 to 0.100" W.C.
<b>Accuracy</b>	+/- 2% of full range
<b>Power Requirements</b>	115 VAC/60Hz
<b>Controls &amp; Display</b>	four digit 3/8" LCD W.C.; display push button for zero and span calibration
<b>Burst Pressure</b>	1 psi
<b>Alarm Set Point</b>	-0.20" W.C.
<b>Housing</b>	durable plastic; (2) sliding locks
<b>Pressure Inlets</b>	(2) 3/16" OD barbed hose connectors; 10' plastic hose provided
<b>Size/Weight</b>	14"W x 3.5"H x 11"L; 4 lbs.