



Manufacturing Equipment for Abatement
and Restoration Industry Since 1988

MiniForce II

HEPA Air Filtration Machine

The OmniAire MiniForce II air scrubber with HEPA filter is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include activated carbon filters for chemical fumes and biological contaminants. The OmniAire MiniForce II provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

OmniAire MiniForce II Specifications


Airflow Ratings (m ³ /m)*	9.2 & 12.0
Operating Speeds	2 speeds
Filtration Stages	HEPA Filter 99.97%, 0.3µs
MERV8 primary/secondary filter
Optional	OdorGuard 600 activated carbon filter
Motor	1/5 hp with Thermal Overload
Circuit Requirements	115V 60Hz 3.2 amps
Pressure Gauge	0-3" W.C.
Cabinetry	Aluminum, silicone sealed before riveting
Exhaust Collar	20cm
Carrying Handles w/Rubber Grips	1
7.6cm Casters.....	4 Swivel
Weight With Filters	19.5kg
Dimensions (cm).....	67.3 L x 35.5 W x 40.6 H

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



ORDERING INFO PART

OmniAire MiniForce II	MF100C
HEPA Filter 99.97%, 0.3µ.....	MFH12
Primary/Secondary Filter (qty 20) ...	MFP1313
Intake Manifold, 20cm.....	MFIM8
Quick Clamp, 20cm	QCW12
Flexible Duct, 20cm x 7.62m	MD8
OdorGuard 600 Carbon Filter	OG1212



The OmniAire MiniForce II comes standard with a particle board 99.97% 0.3µ HEPA filter and can be upgraded to a metal frame 99.99% 0.3µ HEPA filter.

Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

Omnitec Design, Inc.

4640 Campus Place, Suite 110 Mukilteo, WA 98275

Visit us @ www.omnitecdesign.com

Office: 425-290-3922