



Manufacturing Equipment for Abatement
and Restoration Industry Since 1988

OA2200C

HEPA Air Filtration Machine

The OmniAire OA2200C is a construction grade HEPA air scrubber. It delivers the performance of full sized negative air units but is easy to move and set up. Equipped with a 99.97% HEPA filter and 2-stage pre-filter, it is used on asbestos, lead and mold abatement projects. The HEPA filter can be replaced with an economical Bag Filter with high capacity to collect bulk dust from cutting or grinding of concrete, wood or plaster.

OmniAire 2200C SPECIFICATIONS

- Airflow Ratings (m³/m)*..... 28 & 56
- Operating Speeds.....2 Speeds
- Filtration Stages -HEPA Filter 99.97%, 0.3µ
 -MERV 8 primary/secondary filter
- Optional -OdorGuard600 activated carbon filter
 - 9-Pocket Bag Filter, MERV14
- Recessed Controls with:LOW/OFF/HIGH speed switch
 - ...CHANGE FILTER Indicator Light
- Motor1.5 hp with Thermal Overload
- Circuit Requirements**.....115V 60Hz 13.8 amps
- CabinetryAluminum, silicone sealed before riveting
- Exhaust Collar30cm
- Carrying Handles w/Rubber Grips.....4
- 12.7cm Casters 2 Fixed, 2 Swivel
- Weight with Filters64kg
- Dimensions (cm)89L x 66W x 79H

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



ORDERING INFO	PART #
OmniAire 2200C	OA2200C
HEPA Filter 99.97%, 0.3µ	OAH2424L
Primary/Secondary Filter (qty 20)...	OAP2424
Intake Manifold, 30cm	OAIM2200-12
Carbon Vapor Trap Filter.....	OCVT2424
OdorGuard 600 Carbon Filter.....	OG2424
Bag Filter Housing.....	HBF2200
Bag Filter, MERV14.....	OBF10
Flexible Duct, 30cm x 7.62m	OAD12

Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

Omnitec Design, Inc.

4640 Campus Place, Suite 110 Mukilteo, WA 98275
Visit us @ www.omnitecdesign.com
Office: 425-290-3922