



Manufacturing Equipment for Abatement
and Restoration Industry Since 1988

OA2200UL

HEPA Air Filtration Machine

The OmniAire OA2200UL is a construction grade HEPA air scrubber. It delivers the performance of full sized negative air units but is easy to move and set up. Equipped with a 99.97% HEPA filter and 2-stage pre-filter, it is used on asbestos, lead and mold abatement projects. The HEPA filter can be replaced with an economical Bag Filter with high capacity to collect bulk dust from cutting or grinding of concrete, wood or plaster.

OmniAire 2200UL SPECIFICATIONS

- Airflow Ratings (m³/m)*..... 28 & 56
- Operating Speeds.....2 Speeds
- Filtration Stages -HEPA Filter 99.97%, 0.3µ
 -MERV 8 primary/secondary filter
- Optional -OdorGuard600 activated carbon filter
 - 9-Pocket Bag Filter, MERV14
- Recessed Controls with:LOW/OFF/HIGH speed switch
 -0-5" Pressure Gauge
- Motor1.5 hp with Thermal Overload
- Circuit Requirements**.....115V 60Hz 13.8 amps
- Cabinetry Aluminum, silicone sealed before riveting
- Exhaust Collar30cm
- Carrying Handles w/Rubber Grips.....4
- 12.7cm Casters 2 Fixed, 2 Swivel
- Weight with Filters57kg
- Dimensions (cm) 89L x 66W x 79H

*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



| ORDERING INFO | PART # |
|--------------------------------------|-------------|
| OmniAire 2200UL | OA2200UL |
| HEPA Filter 99.97%, 0.3µ | OAH2424L |
| Primary/Secondary Filter (qty 20)... | OAP2424 |
| Intake Manifold, 30cm..... | OAIM2200-12 |
| Carbon Vapor Trap Filter..... | OCVT2424 |
| OdorGuard 600 Carbon Filter..... | OG2424 |
| Bag Filter Housing..... | HBF2200 |
| Bag Filter, MERV14..... | OBF10 |
| Flexible Duct, 30cm x 7.62m | OAD12 |

Optional Accessories



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

Omnitec Design, Inc

4640 Campus Place, Suite 110 Mukilteo, WA 98275
Visit us @ www.omnitecdesign.com
Office: 425-290-3922