



Manufacturing Equipment for Abatement and Restoration Industry Since 1988

OA600N HEPA Air Filtration Machine

The OmniAire OA600N air scrubber with HEPA filter is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include activated carbon filters for chemical fumes and biological contaminants. The OmniAire OA600N provides cleaner and healthier environment at construction/renovation projects and industrial facilities.

OmniAire 600N Specifications

Airflow Ratings (m ³ /m)*	5.5 to 17
Operating Speeds	Variable speed control
Filtration Stages	HEPA Filter 99.97%, 0.3µsMERV8 primary/secondary filter
Optional	OdorGuard 600 activated carbon filter MERV14 GEO95 Filter
Circuit Requirements	115V 60Hz 5.8 amps
GFI Protected Convenience Outlet	8.0 amps
Cabinetry	Flame retardant polyethylene
Exhaust Collar	25cm
Weight With Filters	16.3kg
Dimensions (cm)	63.5 L x 48 H x 48 W

**Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



ORDERING INFO PART

OmniAire 600N	OA600N
HEPA Filter 99.97%, 0.3µm	OAH15156P
Geo95 MERV 14 filter	OAG15154
Primary/Secondary Filter (qty 20)	OAP1616
Quick Clamp, 25cm dia.	QCW12
Flexible Duct, 25cm x 7.62m	OAD10
OdorGuard 600 Carbon Filter	OG1616



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984



Omnitec Design, Inc.

4640 Campus Place, Suite 110, Mukilteo, WA 98275

Visit us @ www.omnitecdesign.com

Office: 425-290-3922