



Manufacturing Equipment for Abatement  
and Restoration Industry Since 1988

# OmniForce II

## HEPA Air Filtration Machine

**The OmniAire OmniForce II air scrubber with HEPA filter is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. Accessories include activated carbon filters for chemical fumes and biological contaminants. The OmniAire OmniForce II provides cleaner and healthier environment at construction and renovation projects and industrial facilities.**

### OmniForce II SPECIFICATIONS

<b>Airflow Ratings (m<sup>3</sup>/m)*</b> .....	11 - 45
<b>Operating Speeds</b> .....	Variable speed control
<b>Filtration Stages</b> .....	HEPA Filter 99.97%, 0.3μ
	.....MERV 8 primary/secondary
<b>Optional</b> .....	OdorGuard 600 activated carbon filter
<b>Recessed Controls</b> .....	High/OFF/Speed Control Switch
	Variable speed controller
	Pressure gauge 0-5"W.C.
<b>Motor</b> .....	1.0 hp. with Thermal Overload
<b>Circuit Requirements**</b> .....	115V/60Hz/10.0 amps
<b>Cabinetry</b> .....	Aluminum, silicone sealed before riveting
<b>Exhaust Collar</b> .....	35cm
<b>Carrying Handles w/Rubber Grips</b> .....	2
<b>3" Casters</b> .....	4 Swivel
<b>Weight with Filters</b> .....	43kg
<b>Dimensions with filter (cm)</b> .....	81L x 46W x 71H

\*Airflows based on blower manufacturer curves. Different HEPA filters may cause the flow to vary.



### ORDERING INFO ..... PART #

OmniForce II .....	OF100V
HEPA Filter 99.97%, 0.3μ .....	OFH12
Primary/Secondary Filter (qty 20) ...	OFP2518
Intake Manifold, 35cm .....	OFM14
Quick Clamp, 35cm .....	QCW14
Flexible Duct, 35cm x 7.62m .....	OFD14
OdorGuard 600 Carbon Filter .....	OG2116



### Optional Accessories



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

## Omnitec Design, Inc.

4640 Campus Place, Suite 110 Mukilteo, WA 98275

Visit us @ [www.omnitecdesign.com](http://www.omnitecdesign.com)

Office: 425-290-3922