



# OMNIFLOW

## Water Filtration System

### ORDERING INFO

OmniFlow  
Water Filter, 20 Micron  
Water Filter, 5 Micron

### PART NUMBER

OWF115  
OWF20  
OWF5



### THE OMNIFLOW IS IDEAL FOR

Abatement  
Remediation Jobs  
Restoration Projects



CONFORMS TO UL STD 507  
CERTIFIED TO CAN/CSA STD  
C22.2 NO. 113-M1984

The OmniFlow is commercial and industrial water filtration system designed for purification of contaminated water at asbestos, lead abatement projects and similar sources at construction sites. Our portable system consists of self priming, positive displacement pump and two filtration stages with 20 and 5 micron filters. The unit is capable of high suction lift and 45 psi discharge pressure. This portable unit has a strong aluminum housing with rubber grip handle and easily accessible hose connections. OmniFlow's two-stage filtration allows for the use of various filter cartridges to meet your requirements. Our standard configuration consists of a 20 $\mu$  and 5 $\mu$  filter.

### The OmniFlow

<b>Flow Capacity</b>	3 gpm
<b>Filtration Stages</b>	50# screen, 20 & 5 micron filters
<b>Water Connection</b>	3/4" male garden hose connection
<b>Power Requirements</b>	115 VAC/60Hz, 1.0 amps
<b>Electrical Protection</b>	circuit breaker
<b>Housing</b>	aluminum, riveted construction
<b>Size/Weight</b>	8"W x 15"H x 23"L; 25 lbs. (with filters)