



The Watchman

Differential Pressure Monitor

ORDERING INFO

Watchman
External Hose Replacement

PART NUMBER

OWDP
IOGHOSE10FT

THE WATCHMAN IS IDEAL FOR

- Abatement/Remediation Jobs
- Restoration Projects
- Construction Sites
- Industrial Areas
- First Response & Epidemic Control
- Bio-Hazard & Crime Scene Clean-up



The Watchman is designed for monitoring differential pressure of 0.020" WC in abatement areas. The protective case contains self-calibrating, precise pressure indicator/transmitter with LCD displays and an audible/visual alarm module. The Watchman is easy to setup for operation: plug into power outlet, push the self-calibrate button and connect the pressure tubing from the containment.

The Watchman

Differential Pressure Range	0 to 0.100" W.C.
Accuracy	+/- 2% of full range
Power Requirements	115 VAC/60Hz
Controls & Display	four digit 3/8" LCD W.C.; display push button for zero and span calibration
Burst Pressure	1 psi
Alarm Set Point	-0.20" W.C.
Housing	durable plastic; (2) sliding locks
Pressure Inlets	(2) 3/16" OD barbed hose connectors; 10' plastic hose provided
Size/Weight	14"W x 3.5"H x 11"L; 4 lbs.