



# OMNIAIRE MiniForce II

## HEPA Air Filtration Machine



### ORDERING INFO

OmniAire MiniForce  
 OmniAire MiniForce 99.99% 0.3µ  
 Primary/Secondary Two-Stage Filters (box of 20)  
 MERV 11 Pleated Filter  
 HEPA Filter 99.99%, 0.3µ (metal frame)  
 HEPA FILTER 99.97%, 0.3µ (pb frame)  
 OdorGuard 600 Carbon Filter  
 Intake Manifold Kit (Manifold, Clamp & 3' Duct)  
 ABS Plastic Intake Manifold, 8" Dia.  
 Quick Clamp, 8"-10" Dia.  
 Flexible Duct, 8" Dia. x 25' L

### PART NUMBER

MF100C  
 MF100CMED  
 MFP1313  
 OPF1212  
 MFH12G  
 MFH12  
 OG1212  
 MFIM8KIT  
 MFIM8  
 QCW12  
 MD8



CONFORMS TO UL STD 507  
 CERTIFIED TO CAN/CSA STD  
 C22.2 NO. 113-M1984

The MiniForce II is a compact, portable HEPA air scrubber built on aircraft-grade aluminum housing, with four non-marking rubber casters, for easy deployment at your jobsite. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial, factory sites and medical facilities. It can be used with multiple filter options such as HEPA, activated carbon plus MERV 9 primary/secondary filter. Additional accessories include intake manifold, flex ducting and quick clamps.

### OmniAire MiniForce II

<b>Airflow*</b>	325/375 CFM
<b>Power Requirements</b>	115VAC/60 Hz/1.6 Amp
<b>Motor</b>	1/5 HP with thermal overload
<b>Controls</b>	speed selector switch - HIGH/OFF/LOW, 0-3" W.C. pressure gauge
<b>Filtration</b>	HEPA filter 99.97% e0.3µ; MERV 9 primary/secondary filter Optional: MERV 11 pleated filter; OdorGuard 600 activated carbon filter; HEPA filter 99.99% 0.3µ
<b>Housing</b>	aircraft grade aluminum; silicone sealed before riveting; 8" outlet; (1) rubber grip handle; (4) 3" hospital grade locking casters
<b>Size/Weight</b>	15"W x 18"H x 27"L; 45 lbs.

\*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.