



# OMNIAIRE 1600PAC

## HEPA Air Filtration Machine

### ORDERING INFO

OmniAire 1600PAC  
 Pleated Filter MERV 11  
 HEPA Filter 99.99%, 0.3 $\mu$  (metal frame)  
 Intake Manifold Kit (Manifold, Clamp & 3' Duct)  
 ABS Plastic Intake Manifold, 12" Dia.  
 Flexible Duct, 10" Dia. x 25' L  
 Quick Clamp 8-12" Dia.  
 Flexible Duct, Wire & Fiber Reinforced  
 UVC Replacement 12" Lamp

### PART NUMBER

OAI1600PAC  
 OPF2416  
 OAH2418G  
 OAIM2000-12KIT  
 OAIM2000-12  
 OAD12  
 QCW14  
 OAD12R  
 EUV12



CONFORMS TO UL STD 507  
 CERTIFIED TO CAN/CSA STD  
 C22.2 NO. 113-M1984

The OmniAire 1600PAC machine is equipped with a medical grade 99.99% HEPA filter and UV-C germicidal lights, which work together to eliminate sub-micron particulates and microbial contamination in healthcare facilities, labs and other critical environments. The 1600PAC features variable air flow, quiet operation, upright housing for a small footprint, and medical grade casters for easy mobility. Additional accessories include PEROx air purification module with hydro-peroxide generators, activated carbon filter, intake/outtake manifold, flex ducting and quick clamps.

### OmniAire 1600PAC

<b>Airflow*</b>	200-1600 CFM
<b>Power Requirements</b>	115VAC/60 Hz/10.6 Amp
<b>UVGI Lights</b>	(4) UV-C 15 watt lamps
<b>Controls</b>	ON/OFF, Variable speed controller; 0-3" W.C. pressure gauge; red power indicator light; UVGI Lights ON/OFF switch; hour meter
<b>Filtration</b>	HEPA filter 99.99% 0.3 $\mu$ ; MERV 11 primary/secondary filter; Optional: MERV 9 primary filter
<b>Housing</b>	aircraft grade aluminum with powder coating; silicone sealed before riveting; (1) rubber grip handle; (4) 3" hospital grade locking casters
<b>Size/Weight</b>	26"W x 40"H x 20"L; 110 lbs.

\*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.