



OmniForce II

HEPA Air Filtration Machine



ORDERING INFO

OmniForce II	OF100V
Primary/Secondary Two-Stage Filters (box of 20)	OFP2518
HEPA Filter 99.99%, 0.3 μ (metal frame)	OAH2424G
HEPA FILTER 99.97%, 0.3 μ (pb frame)	OAH2424L
OdorGuard 600 Carbon Filter	OG2116
ABS Plastic Intake Manifold, 14" Dia.	OFM14
Quick Clamp, 14" Dia.	QCW14
Flexible Duct, 14" Dia. x 25' L	OAD14

PART NUMBER



CONFORMS TO UL STD 507
CERTIFIED TO CAN/CSA STD
C22.2 NO. 113-M1984

OmniAire OmniForce II is a compact and versatile, variable speed HEPA air filtration machine/air scrubber that delivers the performance of full size negative air machines. It is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects, and for purifying air in commercial or factory sites and medical facilities. The light-weight module design allows for the machine to be transported through narrow spaces and quickly set up. Additional accessories include multiple filter options, intake manifold, flex ducting and quick clamps.

OmniForce II

Airflow*	200/1600 CFM
Power Requirements	115 VAC/60 Hz/9.4 Amp
Motor	1 HP with thermal overload
Controls	HIGH/OFF/LOW speed switch; variable speed controller; 0-5" W.C. pressure gauge
Filtration	HEPA 99.97%, 0.3 μ filter; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon filter
Housing	aircraft grade aluminum, silicone sealed before riveting; 14" outlet; (2) rubber grip handles; (4) 3" hospital grade locking casters
Size/Weight	without HEPA, 19"W x 29"H x 21"L, 66 lbs.; with HEPA, 19"W x 29"H x 92"L

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.