



OMNIAIRE 1200PAC

HEPA Air Filtration Machine



UL 507:1997/R:2017-01
CAN/CSA-C22.2 No. 113-15

ORDERING INFO

OmniAire 1200PAC
Pleated Filter MERV 11
HEPA Filter 99.99%, 0.3 μ (metal frame)
OdorGuard 600 Carbon Filter
ABS Plastic Intake Manifold, 10" Dia.
Flexible Duct, 10" Dia. x 25' L
Quick Clamp 12" Dia.
Flexible Duct, Wire & Fiber Reinforced

PART NUMBER

OAI200PACM
OPF1616
OAH1616G
OG1616
OAIM1200P
OAD10
QCW12
OAD10R

The OmniAire 1200PAC machine is equipped with a medical grade 99.99% HEPA filter and UV-C germicidal lights, which work together to eliminate sub-micron particulates and microbial contamination in healthcare facilities, labs and other critical environments. The 1200PAC features variable air flow, quiet operation, upright housing for a small footprint, and medical grade casters for easy mobility. Additional accessories include PEROx air purification module with hydro-peroxide generators, activated carbon filter, intake/outtake manifold, flex ducting and quick clamps.

OmniAire 1200PAC

Airflow*	200-1100 CFM
Power Requirements	115VAC/60 Hz/7.1 Amp
UVGI Lights	(4) UV-C 15 watt lamps
Controls	speed switch - HIGH/OFF/Variable Speed Controller; 0-3" W.C. pressure gauge; red power indicator light; UVGI Lights ON/OFF switch; hour meter
Filtration	HEPA filter 99.99% 0.3 μ ; MERV 11 primary/secondary filter
Housing	aircraft grade aluminum with powder coating; silicone sealed before riveting; (1) rubber grip handle; (4) 3" hospital grade locking casters
Size/Weight	19"W x 42"H x 22"L; 110 lbs.

*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.