

## **EMNIAIRE 1300V**HEPA Air Filtration Machine

ORDERING INFO	PART NUMBER
	FARI NOMBER

**OmniAire 1300V OA1300V** Primary/Secondary Two-Stage Filters (box of 20) **OAP2614** HEPA FILTER 99.97%, 0.3µ (pb frame) **OAH2412** OdorGuard 600 Carbon Filter **OG2412D** ABS Plastic Intake Manifold, 10" Dia. OAIM1300-10 Quick Clamp, 10" Dia. QCW12 Flexible Duct, 10" Dia. x 25' L OAD10 Flexible Duct, Wire & Fiber Reinforced OAD10R





The OmniAire 1300V air scrubber with HEPA filter is used for removal of toxic mold, asbestos and lead dust during renovation and abatement projects. This machine is only 15" wide and ideal for narrow hallways, hotel rooms and condos. Accessories include activated carbon filters for chemical fumes and biological contaminants, as well as intake manifold, flex ducting and quick clamps.

	Ommare 1900V
Airflow*	300/1250 CFM
Power Requirements	115 VAC/60 Hz/8.7 Amp
Motor	1 HP with thermal overload
Controls	HIGH/OFF/speed control switch; variable speed controller; hour meter; 0-5" W.C. pressure gauge
Filtration	HEPA 99.97%, 0.3 μ filter; MERV 9 primary/secondary filter Optional: OdorGuard 600 activated carbon filter
Housing	aircraft grade aluminum, silicone sealed before riveting; 10" outlet; (4) rubber grip handles; (4) 3" hospital grade locking casters
Sizo/Woight	15"W v 30"H v 34"L 03 lbc

\*Airflows based on blower manufacturer curves. Different filters may cause the flow to vary.



OmniAire 1300V